

04.27.00

A

04/25/00



Jc803 U.S. PTO

PATENT

Express Mail: EI 807 287 954 US

Deposited: April 25, 2000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Our Docket No. 990474 U1 USA

James Gilbert
Corbin S. Glenn



Jc675 U.S. PTO
09/558694
04/25/00

For: **"IMPROVED METHOD AND APPARATUS FOR LOCKING
CHARGES INTO A CHARGE HOLDER"**

TRANSMITTAL LETTER

Assistant Commissioner
for Patents
BOX PATENT APPLICATION
Washington, D. C. 20231

Sir:

Attached hereto for filing in the United States Patent and Trademark Office is the patent application identified above, comprising:

1. Specification (with 19 claims)
2. Formal Drawings (8 Sheets)
3. Unsigned Declaration and Power of Attorney
4. Temporary Filing Receipt (return postcard)

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"Express Mail" Mailing Label Number EI 807 287 954 US, Date of Deposit April 25, 2000. I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

ANNIE N. MATHEW
Type or Print Name of Person Mailing

Annie N. Mathew
Signature of Person Mailing

APRIL 25, 2000
Date

The filing fee has been computed as follows:	
Basic Fee	\$ 690.00
Additional Fees:	
Total number of claims (whether Independent or dependent) in Excess of 20, times \$18.00	
	\$ -0-
Number of independent claims, Minus 3, times \$78.00	
	\$ 78.00
TOTAL	\$768.00

Please charge the above computed cost to Deposit Account No. 08-0300. The Commissioner is hereby authorized to charge any additional filing fee which may be required, and credit any over-payment to Deposit Account No. 08-0300. A duplicate copy of this letter is submitted.

In the event the Examiner wishes to contact attorneys of record concerning the merits of the accompanying application prior to the first Office Action, such contact should be made with the undersigned attorney.

Very truly yours,

HALLIBURTON ENERGY SERVICES, INC.



By: WILLIAM M. IMWALLE
Registration No. 35,904

Date: April 25, 2000

Enclosures

P. O. Box 819052
Dallas, Texas 75381-9052
Telephone: (972) 418-3886

APPLICATION FOR
UNITED STATES LETTERS PATENT

FOR

IMPROVED METHOD AND APPARATUS FOR LOCKING
CHARGES INTO A CHARGE HOLDER

By:

JAMES GILBERT and
CORBIN S. GLENN

Certificate under 37 CFR 1.10 of Mailing by "Express Mail"

EI 807 287 954 US

"Express Mail" label number

APRIL 25, 2000

Date of Deposit

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Annie N. Mathew

Signature of person mailing correspondence

ANNIE N. MATHEW

Typed or printed name of person mailing correspondence

IMPROVED METHOD AND APPARATUS FOR LOCKING CHARGES INTO A CHARGE HOLDER

Technical Field of the Invention

The present invention relates to an improved method and apparatus for locking shape charges into a charge holder for use in well perforation operations. The improved apparatus eliminates the need to bend tabs on the charge holder to hold the charges in position.

Background of the Invention

The performance of an underground well, such as a hydrocarbon producing well, can be improved by perforating the formation containing the hydrocarbons. Well perforation operations involve the controlled detonation of shape charges within the well. The shape charges perforate the casing, if any, and the surrounding formation, thereby improving the flow of hydrocarbons from the well. A perforation gun is used to hold the shape charges. The perforation gun is lowered into the well on either tubing or a wireline until it is at the depth of the formation of interest. The gun assembly includes a charge holder that holds the shape charges and a carrier that protects the shape charges from the environment. A detonation cord links each charge located in the charge holder.

A shaped charge is inserted into a mating hole of the charge holder, and a charge retention apparatus holds the charge firmly within the mating hole. The charge retention apparatus normally include retaining rings, charge retention jackets, clips, or bending tabs, all of which are designed to secure the shaped charge in the charge holder. Thus, it is desirable to provide a method and apparatus for securing the shaped charge to the charge holder of a perforating gun without using a separate charge retention apparatus or bendable tabs.

An example of a common charge retention design is shown in **Figures 1 to 5**. A perforation gun 10 is shown having a charge holder 12 and a cover (not shown). The charge holder has at least one opening 16 for receiving the shape charge 18. Each shape charge 18 has a case 20 that is generally conical in shape. An explosive charge is nestled into the case 20. Most cases 20 also have a pair of tabs 22 that retain the

detonation cord 24. The detonation cord 24 can ignite the explosive charge through a detonation transfer passage 32 through the case 20. The carrier can have scalloping 26 that corresponds to the location of each charge. The scalloping is an area of reduced thickness used to minimize any resistance to the exploding shape charge.

The gun is assembled by sequentially placing the charges 18 into the charge holder 12. Once inserted, the charge must be secured in place. At least one deformable tab 30 can be used. The tip of a tool such as a screw driver is inserted into slot 28, as shown in **Figure 2**, and the tab 30 is deformed until it is in contact with the front of the charge case. There are obvious drawbacks to such a retention scheme. For one, fabrication of the slot 28 is expensive and time consuming. The charge holders 12 are typically made of steel and the slots require an additional fabrication step to cut. Further, the deformation of the tab 30 takes additional assembly time. It also causes a minor deformation to the rest of the charge holder. When many tabs are deformed, the overall charge holder can experience a meaningful length increase. The deformation of the charge holder can also cause a misalignment of the charges and scalloping 26 on the carrier. Equally troublesome is the inability to easily disassemble the loaded charge holder. If the perforation gun is lowered into a well and for an unknown reason fails to fire, the gun is removed from the well and disassembled. This requires a worker to remove the charge holder from the carrier and then use a tool to undeform the tabs 30 to remove the charge. The use of the tool around the live charges introduces a safety concern. Also, once disassembled, the charge holder is unusable and must be scrapped.

A need exists for an easier and less expensive method to load charges into a charge holder. Such a method should use an improved charge holder design that does not require the use of deformable tabs. One attempt at making such a charge holder is shown in U.S. Patent No. 5,952,603 to Parrott and entitled "Insert and Twist Method and Apparatus for Securing a Shaped Charge to a Loading Tube or a Perforating Gun." Rather than the use of tabs, Parrott '603 discloses the use of specially designed lugs on the charge case. In **Figures 6 and 7** illustrate an embodiment of the Parrott '603 design. A shaped charge case 52 is inserted into a mating hole 54 of a loading tube 50 prior to inserting the loading tube in a perforating gun carrier. The pair of retaining lugs 52a are inserted into slots 54a and 54b of the mating hole 54 and, simultaneously, the pair of

shoulder lugs 52c are inserted into the first and second pair of grooves 54c and 54d, the lugs 52c being initially inserted into the large diameter groove L associated with the first and second pair of grooves 54c, 54d. At this point, a wrench is required. The wrench is secured to the pair of support lugs 52b and twisted clockwise. The clockwise torque provided by the wrench on the support lugs 52b moves the shaped charge case 52 in a clockwise circumferential direction.

In **Figure 7**, during the movement of the shaped charge case 52 in the clockwise circumferential direction, an end portion of the retaining lugs 52a move underneath a surface of the loading tube 50. Simultaneously, the pair of shoulder lugs 52c move out of the large diameter groove L of the pair of grooves 54c and 54d and into the small diameter groove S of the pair of grooves 54c and 54d. In this position, the surface of the loading tube 50 prevents the retaining lugs 52a of the shaped charge case 52 from moving in an outward radial direction; and the small diameter groove S prevents the shoulder lugs 52c from moving in an inward radial direction. In addition, the small diameter groove S of the first and second pair of grooves 54c and 54d prevents the shaped charge case 52 from moving either clockwise or counterclockwise in a circumferential direction.

The Parrot '603 design is exceedingly difficult and expensive to fabricate. For example, most charge cases are made of either steel or zinc. To place the lugs on a steel case requires a welding step or a very expensive lathing process. Zinc can be cast, and therefore to be cost effective, one is essentially limited to the use of a zinc case. Therefore, a need exists for a simpler and less expensive apparatus for holding shape charges in a carrier. Such an apparatus should not require expensive milling steps to construct and should quick to assemble and disassemble. In the event of disassembly, the carrier should be reusable.

Summary of the Invention

The present invention addresses many of the drawbacks found in prior art retention schemes. In one embodiment, the invention uses a pair of opposed tabs on the carrier to engage a groove in the case of the shape charge. The case is generally conical in shape. However, the front opening of the case has both a first and second circumferential ridge separated by a groove. The diameter of the groove generally matches the distance between tabs. The second ridge can have a flat milled thereon to allow case to be inserted until the tabs contact the forward or first ridge. This locates the tabs between the first and second ridges and over the groove. The case is then rotated so that the tabs are captured between the two ridges. In another embodiment, there is no forward ridge, and the tab only contacts the rear ridge.

Once installed, the detonation cord is attached to the case. The cord helps prevent any rotation of the case, thereby securing it into the charge holder. Thus, the use of easily milled tabs on the charge holder in conjunction with an easily milled groove and flats on the case provide an improved apparatus and method for securing the shape charge into the charge holder of a perforation gun. When the charges are all installed, and the detonation cord is properly linked between each charge, then the charge holder can be placed in a carrier.

If a need arises for disassembling the perforation gun, the charge holder can be removed from the carrier. The detonation cord is then uncoupled from the charges to be removed. The charge case can then be simply turned until the tabs on the charge holder are aligned with the flats on the first ridge. The charge case is then pulled from the charge holder, leaving the charge holder in condition to be used again. No tools are required for this operation.

Brief Description of the Drawings

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an exploded view of a prior art charge holder tube with deformable tabs and shape charge cases shown aligned with holes in the charge holder;

Figure 2 is a perspective of a charge holder tube assembly showing a shape charge case installed and the tab being deformed by a tool;

Figures 3 and 4 are sectionals showing the detonation cord connected between tabs on the rear of each case;

Figure 5 shows a cut-away view of a scalloped case over the charge holder shown in Figures 1 to 4;

Figures 6 and 7 illustrate another prior art charge holder design that utilizes lugs on the shape charge case;

Figure 8 is an exploded view of one embodiment of the present invention wherein tabs are located on the charge holder that engage a groove on the shape charge case;

Figure 9 is a side sectional view of one embodiment of the case for a shape charge in accordance with the present invention; and

Figure 10 is a side sectional view of another embodiment of the case for a shape charge.

Detailed Description of the Drawings

The present invention overcomes the disadvantages of prior art perforation gun assemblies by being easy to fabricate, easy to assemble, and easy to disassemble. Referring to **Figures 8 and 9**, an embodiment of the present invention is disclosed. The perforation gun assembly 100 comprises a charge holder 102 that contains at least one shape charge 104. The charge holder is typically a cylindrical loading tube having a plurality of holes, and at least one hole, disposed through its wall. Each shape charge 104 is formed by a case 106 that can contain an explosive charge. The case 106 is generally conical in shape with a narrowed end that is received into a hole 108 in the charge holder 102. The narrowed end of each case includes a detonation cord receiver 110 for receiving a detonation cord. A passage 120 through the wall of the case allows the detonation cord to ignite the explosive charge within the case.

The charge holder 102 can have a plurality of holes 108 for receiving a plurality of shape charges 104. However, not every hole must be used. Indeed, the spacing of the holes can vary significantly according the firing pattern desired for a particular formation. It is common for the charges to be placed in an angular pattern; although, a single straight line of charges may be appropriate in some circumstances as well. Further, the number of charges per linear foot of carrier is also an important criteria. It is common for a well engineer to specify between four to six charges per foot of carrier.

Each hole 108 is defined by a uniquely shaped circumference 112. The circumference 112 has at least one tab 114. The charge holder shown in **Figure 8** has two tabs per hole; however, more could be used. In one embodiment, the case 106 can have a first ridge 116 and a second ridge 118 around its circumference. The first ridge 116 is forward from the second ridge 118. A groove 122 is defined between the two ridges. Moreover, the second ridge 118 has a flat 124 that corresponds to each tab 114. **Figures 7 and 8** illustrate an embodiment for the present invention wherein two tabs 114 are placed opposite each other on the circumference 112. The distance between the ends of each tab 114 can closely approximate the diameter of the groove 122. Likewise, the width of the tabs 114 can closely approximate the width of the groove 122.

The flats 124 allow the tabs to pass over the second ridge 118 until they contact the first ridge 116. Of course, a flat is simply one geometry to allow the tab to enter the

groove. A complementary shape cut could also allow the tab to pass over the forward ridge and into the groove. Once the tabs 114 are in the groove 122, a simple rotation of the case 106 captures the tabs between the first and second ridges, thereby preventing the case from disengaging the charge holder 102. The detonation cord is then coupled to the cord retainer on the case. This minimizes the risk of the case rotating to a position where the tabs and flats are again adjacent. Once the charges are installed into the charge holder, a carrier (not shown) may be placed over the charge holder to protect the integrity of the shaped charges.

The use of tabs on the circumference of each hole 108 is far easier to manufacture than a deformable tab or lugs on the charge case. Most charge holders can be laser cut. The present invention only requires a modification to the circumference of each hole and does not require the cutting of an additional slot. Another feature of hole 108 can be a reduced diameter portion 130. This feature can provide added stability to the individual charge cases. In one embodiment, shown in **Figure 10**, the case does not have a forward ridge 116. Instead, the case has only the rear ridge 118. In this embodiment, the case can not move in the direction of arrow A because of contact between the tab 114 and surface 118a of rear ridge 118. Likewise, the case can not move in the direction of arrow B because of contact between surface 118b of rear ridge 118 and reduced diameter portion 130. With either embodiment, the case is secure in the loading tube.

Although preferred embodiments of the present invention have been described in the foregoing detailed description and illustrated in the accompanying drawings, it will be understood that the invention is not limited to the embodiments disclosed but is capable of numerous rearrangements, modifications, and substitutions of steps without departing from the spirit of the invention. Accordingly, the present invention is intended to encompass such rearrangements, modifications, and substitutions of steps as fall within the scope of the appended claims.

We claim:

1. A charge holder for accepting an explosive charge in a case, said charge holder comprising:
a loading tube including at least one hole disposed through a wall of said loading tube, said hole having a circumference defining at least one tab.
2. The charge holder of Claim 1 wherein said case comprises a rear ridge.
3. The charge holder of Claim 1 wherein said case comprises a first and second ridge defining a groove between, and wherein said tab can be captured within said groove.
4. The charge holder of Claim 3 wherein said case further comprises a flat to allow the at least one tab access to said groove.
5. The charge holder of Claim 1 wherein said case further defines a cord retainer for retaining a detonation cord.
6. The charge holder of Claim 3 wherein the circumference has a diameter approximately equal to a diameter of the first ridge.
7. The charge holder of Claim 3 wherein said tab has a length approximately equal to a depth of the groove.

8. A perforation gun comprising:
- (a) a charge holder for accepting at least one explosive charge stored in a case;
 - (b) a cover for use over the charge holder; and
 - (c) a detonation cord for connecting the at least one explosive charge to a detonation source;
- wherein the charge holder comprises a loading tube including at least one hole disposed through a wall of said loading tube, said hole having a circumference defining at least one tab.
9. The perforation gun of Claim 8 wherein said case has a rear ridge.
10. The perforation gun of Claim 8 wherein said case comprises a first and second ridge defining a groove between, and wherein said tab can be captured within said groove.
11. The perforation gun of Claim 10 wherein said case further comprises a flat to allow the at least one tab access to said groove.
12. The perforation gun of Claim 8 wherein said case further defines a cord retainer for retaining a detonation cord.
13. The perforation gun of Claim 10 wherein the circumference has a diameter approximately equal to a diameter of the first ridge.
14. The perforation gun of Claim 10 wherein said tab has a length approximately equal to a depth of the groove.

15. A method of loading a perforation gun comprising the steps of:
- (a) inserting at least one explosive charge in a case into a charge holder
- comprises a loading tube including at least one hole disposed through a wall of said loading tube, said hole having a circumference defining at least one tab; and wherein the case has a groove for accepting the tab; and
- (b) rotating the case to capture the tab within the groove.
16. The method of Claim 15 further comprises:
- (c) attaching a detonation cord to a cord retainer on the case.
17. The method of Claim 15 further comprises:
- (c) placing a cover over the charge holder.

18. A method of perforating a well comprising the steps of:

(a) loading a carrier holder with at least one explosive charge in a case, wherein the charge holder has at least one hole disposed through a wall, said hole having a circumference defining at least one tab; and wherein the case has a groove for accepting the tab;

(b) rotating the case to capture the tab within the groove.

(c) attaching a detonation cord to a cord retainer on the case.

(d) lowering the carrier holder into the well; and

(e) detonating the at least one explosive charge.

19. The method of Claim 17 further comprises placing a cover over the charge holder before lowering the carrier holder into the well.

IMPROVED METHOD AND APPARATUS FOR LOCKING CHARGES INTO A CHARGE CARRIER

Abstract

The invention uses a pair of opposed tabs on the charge holder to engage a groove in the case of the shape charge. The case is generally conical in shape. However, the front opening of the case has both a first and second circumferential ridge separated by a groove. The diameter of the groove generally matches the distance between tabs. The second ridge can have a flat milled thereon to allow case to be inserted until the tabs contact the forward or first ridge. This locates the tabs between the first and second ridges and over the groove. The case is then rotated so that the tabs are captured between the two ridges. Once installed, the detonation cord is attached to the case. The cord helps prevent any rotation of the case, thereby securing it into the charge holder. Thus, the use of easily milled tabs on the charge holder in conjunction with an easily milled groove and flats on the case provide an improved apparatus and method for securing the shape charge into the charge holder of a perforation gun. When the charges are all installed, and the detonation cord is properly linked between each charge, then the charge holder can be placed in a carrier.

005210" 16325560




FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)

005270-16935560




FIG. 3
(PRIOR ART)




FIG. 4
(PRIOR ART)





FIG. 5
(PRIOR ART)

005210" 16935550








FIG. 8





DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

This declaration is of the following type:

- ☒ (X) original
- ☐ () design
- ☐ () supplemental
- ☐ () national stage of PCT

My residence, post office address, and citizenship are as stated below next to my name, I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

“Improved Method and Apparatus For Locking Charges Into a Charge Holder”

the specification of which: (check one)

- ☒ (X) is attached hereto.
- ☐ () was filed on , as Application Serial No. , and was amended on -- (if applicable)
- ☐ () was described and claimed in PCT International Application No. -- filed on -- and as amended under PCT Article 19 on -- (if any).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information known to be material to the patentability of any claim in accordance with Title 37, Code of Federal Regulations, §1.56, and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable examiner would consider it important in deciding whether to allow the application to issue as a patent.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S)

<u>Number Claimed</u>	<u>Country</u>	<u>Day/Month/Year Filed</u>	<u>Priority</u>
---------------------------	----------------	-----------------------------	-----------------

- NONE -

☐ Yes ☐ No

☐ Yes ☐ No

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below:

<u>Number Claimed</u>	<u>Month/Day/Year Filed</u>
-----------------------	-----------------------------

This declaration is of the following type: (if applicable)

- ☐ divisional
- ☐ continuation
- ☐ continuation-in-part(CIP)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

<u>Application Serial No.</u>	<u>Filing Date</u>	<u>Status Patented/Pending/Abandoned</u>
-----------------------------------	------------------------	--

- NONE -

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: WILLIAM E. SHULL, Reg. No. 29,438; PAUL I. HERMAN, Reg. No. 37,349; WILLIAM M. IMWALLE, Reg. No. 35,904; WILLIAM R. PEOPLES, Reg. No. 25,906, ROBERT A. KENT, Reg. No. 28,626; EUGENE R. MONTALVO, Reg. No. 32,790 and CRAIG W. RODDY, Reg. No. 36,256 of HALLIBURTON ENERGY SERVICES, INC., P. O. Box 819052, Dallas, Texas 75381-9052 and DAVID W. CARSTENS, Reg. No. 34,134, and RUDOLPH J. BUCHEL, JR., Reg. No. 43,448, Carstens Yee & Cahoon, LLP, P.O. Box 802334, Dallas, Texas 75380.

SEND CORRESPONDENCE TO:

David W. Carstens
 CARSTENS YEE & CAHOON, LLP
 P.O. Box 802334
 Dallas, Texas 75380

DIRECT TELEPHONE CALLS TO:

David W. Carstens
 (972) 997-7290

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1	William James Gilbert, Jr.		
	Full Name	Inventor's Signature	Date
	8301 C.R. 1206 Rio Vista, Texas 76093 Residence		U.S.A. Citizenship
2	8301 C.R. 1206 Rio Vista, Texas 76093 Post Office Box		
	Corbin Glenn		
	Full Name	Inventor's Signature	Date
	1009 Bryant Benbrook, Texas 76126 Residence		U.S.A. Citizenship
	1009 Bryant Benbrook, Texas 76126 Post Office Box		